

PYRO-SAFE FLAMMOPLAST KS 3

Intumescent fire protection filler.

Subject to errors, typographical errors and modifications. The specified details reflect the state of the art / the effective standard at the time of printing (09/2014). Please let us know when you need information about the legal and technical requirements or the manufacturer's specification that apply to your specific case. © Copyright svt Unternehmensgruppe, Seevetal. PYRO-SAFE is a registered trademark © of svt Unternehmensgruppe, Seevetal.



Product description

Fields of application

Intumescent fire protection filler on water-based dispersion for indoor use. Approved product for cable, pipe and combined penetration sealings.

Product features

Solvent-free and non halogen.

Fire rating of systems

Up to 2 hours

Applicability certificate

Tested and approved according to national and international standards as e.g.: DIN, other standards on request

Pipes

Cables

Technical Data

Handling

- The surface has to be dry, dust-free und free of grease.
- The application is done by filling.
- The consumption depends on the size of the opening.

Ordering information

PE-pails of 12.5 kg and 15 kg

Storage

Protect the product from frost!

Cool and dry (+5 °C up to +25 °C).

Safety instructions

Please refer to our MSDS (safety data sheet).

Technical data

Colour	white
Density (+ 20 °C)	1.20 - 1.38 g/cm ³
Viscosity (+ 20 °C)	paste-like
Volatile content	< 140 g/l
Drying time (at +23°C / 65% ± 3% rel. humidity)	Dust dry: min. 8 hours Thoroughly dry: min. 10 days (depends on film thickness)
Processing temperature	≥ +5 °C

Applied systems

- PYRO-SAFE Novasit
- PYRO-SAFE Universal
- PYRO-SAFE Bag
- PYRO-SAFE Pipe seals for combustible pipes
- PYRO-SAFE Pipe seals for non-combustible pipes