

# Loose mineral fibre wool

Subject to errors, typographical errors and modifications. The specified details reflect the state of the art / the effective standard at the time of printing (09/2014). Please let us know when you need information about the legal and technical requirements or the manufacturer's specification that apply to your specific case. © Copyright svt Unternehmensgruppe, Seevetal PYRO-SAFE is a registered trademark © of svt Unternehmensgruppe, Seevetal.



## Product information

### Fields of application

Mineral Fibre Wool is used to plug voids and slots of fire protection sealing system for cables, pipes or combined penetrations as well as joints in walls and floors.

### Product features

Heat insulating, sound absorbing, water vapor permeable, ageing resistant, chemically neutral, easy and quick to use.

### Fire rating of systems

Up to 4 hours

### Applicability certificate

Tested and approved according to national and international standards as e.g.:  
DIN, other standards on request

Pipes

Cables

## Technical Data

---

### Handling

Application by hand according to the requirements of the compacted apparent density.

### Ordering information

Bag of 10 kg

### Storage

Cool and dry (+5 °C up to +25 °C).

### Consumption

The consumption is based on the size of the opening.

### Safety instructions

Please refer to our MSDS (safety data sheet).

### Technical data

<b>Colour</b>	grey-green
<b>Form</b>	ffibrous
<b>Melting point</b>	≥ 1.000 °C
<b>Compacted apparent density</b>	approx. 50 - 120 kg/m <sup>3</sup>
<b>Consumption for 10 mm density</b>	compacted apparent density in kg/m <sup>3</sup> 50 100 120 approx. quantity in kg/m <sup>2</sup> 0.5 1.0 1.2

### Applied systems

---

- Various PYRO-SAFE fire penetration sealing systems