

PYRO-SAFE BIOBAG

Fire protection bags

Subject to errors, typographical errors and modifications. The specified details reflect the state of the art / the effective standard at the time of printing (09/2014). Please let us know when you need information about the legal and technical requirements or the manufacturer's specification that apply to your specific case. © Copyright svt Unternehmensgruppe, Seevetal
PYRO-SAFE is a registered trademark © of svt Unternehmensgruppe, Seevetal.



Product information

Fields of application

Reusable fire protection bags to close openings in walls and floors.
Approved product for temporary and permanent cable penetration sealing systems.

Product features

Bags are made of high temperature resistant mineral wool with a covering of nonflammable glass fibre; reusable, flexible, aging resistant, dust-free installation.

Fire rating of systems

Up to 1½ hours according to DIN 4102-9

Applicability certificate

Tested and approved according to national and international standards as e.g.:
DIN, other standards on request

Cables

Technical Data

Handling

- Easy installation without tools
- Working temperature > + 5 °C

Ordering information

Packing in carton.

- Size 0: 125 pieces per carton
- Size 1: 80 pieces per carton
- Size 2: 35 pieces per carton

Storage

Cool and dry (+5 °C up to +25 °C).

Safety instructions

Please refer to our MSDS (safety data sheet).

Technical data

Dimensions	Size 0: 150 x 200 x 40 mm Size 1: 300 x 200 x 40 mm Size 2: 300 x 200 x 100 mm
Consumption	Size 1: approx. 120 pieces/m ² Size 2: approx. 50 pieces/m ²
Nominal bulk density	50 - 60 kg/m ³
Melting point	≥ 1.000 °C

Applied systems

- PYRO-SAFE Novasit
- PYRO-SAFE Bag