





FLAMRO® BK-N Pad seal

Penetration seal made of pad seals for temporary or permanent closure of cable glands.



Allowed services

Media lines		max. diameter*
	Cable	≤ 80
	Cable bundle	≤ 100 / ≤ 21
	Cable support structures	✓
	Empty plastic/steel pipes	≤ 16

*All specifications in mm

Fire resistance class

max. EI 180 acc. to EN 13501-2

Field of Application

- Plasterboard wall, solid wall, floor

System data

Certificate of usability		ETA-17/0904
Thickness structural element	Wall	≥ 100
	Floor	≥ 150
Sealing thickness	Wall	≥ 250
	Floor	≥ 250
Maximum sealing size	Wall	600 x 600
	Floor	600 x 600

All specifications in mm

Products



FLAMRO® BK-N Pad seal

BK-N S 250 x 60 x 30 mm - Art. no. 12060
BK-N M 250 x 130 x 35 mm - Art. no. 12130
BK-N L 250 x 180 x 35 mm - Art. no. 12180

Please contact us for further information:

Information: global@svt.de Orders: order@svt.de
+49 4105-40 90-0

Errors, misprints and changes reserved. All specifications reflect the state of the art or the version of the standard applicable at the time of going to press (06.2020). We will gladly provide you with information on request regarding the legal and technical framework conditions or manufacturer specifications applicable to your individual case. © Copyright FLAMRO®-Brandschutz-Systeme GmbH, Seevetal. FLAMRO® is a registered trademark © of FLAMRO® Brandschutz-Systeme GmbH, Seevetal.