



PYRO-SAFE® ES

Plasterboard penetration sealing system made of mineral wool and ablative filler.



Fire resistance class

max. EI 120 acc. to EN 13501-2

Field of Application

- Plasterboard wall, solid wall, floor

System data

Certificate of usability		ETA-14/0418
Thickness structural element	Wall	≥ 100
	Floor	≥ 125
Sealing thickness	Wall	≥ 100
	Floor	≥ 125
Maximum sealing size	Wall	350 x 150 (angular) or Ø 150 (round)
	Floor	350 x 150 (angular) or Ø 160 (round)

All specifications in mm

Allowed services

Media lines		max. diameter*
	Cable	≤ 21
	Cable bundle	≤ 100 / ≤ 21
	EIC Single	≤ 32 / ≤ 21
	EIC Bundle	≤ 100 / ≤ 32 / ≤ 21
	Combustible pipes	≤ 32
	HVAC split-line-combinations	✓

*All specifications in mm

Please contact us for further information:

✉ Information: global@svt.de Orders: order@svt.de
☎ +49 4105-40 90-0



PYRO-SAFE® ES

Products



PYRO-SAFE® FLAMMOTECT-A **Fire protection coating**

Coating

12,5 kg Pail - Art. no. 01155101

15 kg Pail - Art. no. 01155105

Solid emulsion

12,5 kg Pail - Art. no. 01155106

15 kg Pail - Art. no. 01155107

Filler

12,5 kg Pail - Art. no. 01155104


15 kg Pail - Art. no. 01155109

310 ml cartridge - Art. no. 01155125



Mineral wool

Bag of 10 kg - Art. no. 01183000



PYRO-SAFE® DG-CR 1.5 **Fire protection wrap**

Roll of 10 m x 125 mm - Art. no. 01261125
