

Fire behaviour A1 (non-combustible) in accordance with EN 13501-1

Product Description

ROKU® V8 Gypsum Boards are made from various types of plaster and added cellulose fibres. The boards are heavy-duty, harmless regarding to building biology and have a high edge stability



Application Areas

- as surface insulation in fire protection doors
- indoor areas
- suitable for wet rooms
- as insulation for tubular frame constructions

Technical Data

Composition:	hardened natural gypsum with cellulose
Material structure:	firm panel material
Surface texture:	smooth on both sides
Bulk density [kg/m³]:	approx. 1100–1250
Thermal conductivity [W/m·K]:	0.280 ¹⁾
pH value:	7

Supply Formats

Length:	3030 mm (special lengths available upon request)
Width:	1270 ± 1.0 mm (special widths available upon request)
Thicknesses:	12.5 mm / 15 mm / 18 mm / 22 mm (special thicknesses available upon request)

The cut formats (lengths × widths) are manufactured on the basis of the general tolerance DIN ISO 2768-1-c.

Please observe the safety data sheet.

Processing and Storage

Processing	Ensure that dust is minimised.
Storage	Store in a dry area between -20 °C and +50 °C.

Note

The information in this brochure is based on our knowledge and experience to date. This information does not release the user from carrying out independent tests and trials due to the various influences when processing and applying our product. It is not possible to derive a guarantee of certain properties or suitability of the product in a concrete application case based on our information. All the descriptions, drawings, photographs, data, conditions, weights etc. included may change without previous announcement; they do not constitute the contractually agreed property of the product. The recipient of our product is responsible to observe any trademark rights and existing laws and regulations.

¹⁾ DIN 12664:2001-05