



GEAQUELLO® E 824

Impregnation fluid

Description

Impregnation fluid GEAQUELLO® E 824 for GEAQUELLO® systems E 795 and E 950.
GEAQUELLO® E 824 is an aqueous solution of colloidal silicic acid.

Areas of Application

- Ships & offshore
- Rolling stock
- In the sealing system GEAQUELLO® E 950
- In the sealing system GEAQUELLO® CPS
- In the sealing system GEAQUELLO® E 795



Delivery and Packaging

GEAQUELLO® E 824		
Packaging	Bottle	Can
Size	à 1 kg	à 10 kg
Article number		
	4145152	4145286

Please contact us for further information:

+49 561 5801-0
+49 4105-40 90-14

ships@svt.de
industry@svt.de



GEAQUELLO® E 824

Technical Data

Application instructions	
<ul style="list-style-type: none"> • Used for the impregnation of retaining modules. • A spray cap for the 1 kg bottles is available. • Use gloves and eye protection while working. • Cover the work place with paper or foil. 	
Product properties	<ul style="list-style-type: none"> • reacts neutrally • physiologically safe • not subject to hazard identification requirements
Colour	blue
Viscosity	< 10 mPa·s
Density	approx. 1.1 g/cm ³
pH value (10 % solution)	7.0–8.0
Conductivity (10 % solution)	450–600
Boiling point	approx. 100 °C
Melting point	approx. 0 °C
Storage	Protect from frost! Cool and dry storage. Shelf life of at least 24 months in sealed original packaging.
Safety instructions	Consult the safety data sheet for additional instructions.