



Protect your values.

PYRO-SAFE® BIOBAG

Pad seal

Description

Pad seal made of non-combustible glass fabric, filled with mineral wool. Reusable and flexible can be used for temporary or permanent penetration sealing.

Application areas

- Cable penetration seals in walls and floors with frequent changes in cable assignment.
- For use as a permanent or temporary penetration seal.
- As a back-up.
- Dust-free installation.



Delivery and packing

PYRO-SAFE® BIOBAG			
Packing	Cardboard box		
Size	Size 0	Size 1	Size 2
		(150 x 200 x 40 mm)	(300 x 200 x 40 mm)
Quantity	125 pcs.	80 pcs.	35 pcs.
Item number			
	01170000	01171000	01172000

Please contact us for further information:

✉ global@svt.de

Orders: order@svt.de

☎ +49 4105-40 90-0



Protect your values.

PYRO-SAFE® BIOBAG

Technical data

Density	50 – 60 kg/m ³		
Melting point	≥ 1,000 °C		
Sizes, dimensions and consumption	Size 0	150 x 200 x 40 mm	for small openings and for filling e.g. in and around cable trays
	Size 1	300 x 200 x 40 mm	approx. 120 pieces/m ²
	Size 2	300 x 200 x 100 mm	approx. 50 pieces/m ²
Application instructions	Easy installation without tools.		
Storage	In a cool and dry place (+5 °C to +25 °C)		
Safety information	Please note our safety data sheet.		

Applications

Penetration seal

	Certification	System name	Fire resistance class
	Z-19.53-2377	PYRO-SAFE® Bag	Fire-resistant (90 min.)
	Z-19.53-2373	PYRO-SAFE® Novasit 90	