



Protect your values.

PYRO-SAFE® BIOFERM S

Sealants

Description

Permanently elastic, vibration and temperature resistant fire protection silicone.

Application areas

- Preventive fire protection, elastic and pressure-tight sealing of non-combustible pipes in wall and floor feedthroughs.
- Flexible sealing of structural joints in indoor and outdoor areas.



Delivery and packing

PYRO-SAFE® BIOFERM S		
Packing	Cartridge	Cartridge
Coating	Grey	White
Container size	310 ml	310 ml
Item number		
	01156031	01156032

Please contact us for further information:

✉ global@svt.de

Orders: order@svt.de

☎ +49 4105-40 90-0



Protect your values.

PYRO-SAFE® BIOFERM S

Technical data

Coating	Grey or white
Bulk density	approx. 1.43 kg/dm ³
Tensile strength (ISO 8339)	approx. 0.4 N/mm ²
Tear resistance (notch strength)	approx. 4.3 N/mm ²
Shore A hardness	approx. 22
Perm. max. total deformation	According to DIN 18540: approx. 25 %
Temperature resistance	-50 °C to +150 °C
Movement absorption on pipe penetration seals	Radially: ± 10 % of the original joint width Axially: ± 20 % of the original joint width
Application temperature	+5 °C to +40 °C
Skin formation (23 °C/50 % relative humidity)	approx. 20 min.
Application instructions	The adhesive surfaces must be dry, load-bearing and free of dust and grease.
Consumption	With one cartridge for joint dimensioning of: 5 x 5 mm – approx. 12 linear metres 10 x 10 mm – approx. 3 linear metres
Storage	Protect from frost! Store in a cool and dry place (+5 °C to +25 °C). Can be stored for at least 18 months in sealed original containers.
Safety information	Please note our safety data sheet.

Applications

Penetration seal

	Certification	System name	Fire resistance class
	abP P-NDS04-769	PYRO-SAFE® BIOFERM S	-

Errors, misprints and changes reserved. All of the information corresponds to the state of technology and the version of the standard that existed at the time of printing (02.2021). We will gladly provide you with information on request regarding the legal and technical framework conditions or manufacturer specifications applicable to your individual case. © Copyright svt Unternehmensgruppe, Seevetal. PYRO-SAFE® is a registered trademark ® of the svt group, Seevetal.