

GEAQUELLO® Front wall package 120

Retaining modules and impregnation liquid

Description

The GEAQUELLO® front wall package 120 contains 120 R 312 and four R 380 modules as well as the impregnation liquid E 824. The retaining modules serve as permanent formwork and spacers between cables and the connector wall. The impregnation liquid causes them to expand and become fire-retardant. Vertical openings require one end wall, for horizontal openings two walls are required.

Areas of Application

- Ships & offshore
- In the sealing system GEAQUELLO® E 950
- In the sealing system GEAQUELLO® CPS



Delivery and Packaging

GEAQUELLO® Front Wall Package 120		
Packaging	box	
Modules	R 312	R 380
Number of pcs.	120	4
Liquid	E 824	
Weight / container	4 kg-Flasche incl. spray attachment	
Article number		
	4137310	

Please contact us for further information:

+49 4105-40 90-14

transportation@svt.de



Technical Data

R 312 / R 380	
Application instructions	
<ul style="list-style-type: none"> The material can be trimmed to size using ordinary cutting tools such as scissors or cutter knives. A module must be wrapped around each cable/pipe. This ensures that the sealing compound fills the complete penetration. Vertical openings require one end wall, for horizontal openings two end walls are needed. After installation the impregnation liquid GEAQUELLO® E 824 is applied to the modules, causing them to expand and become fire-retardant. To protect from humidity, a coating of FLAMMADUR® E 292, E 292 T, A 365 may be applied. 	
Product properties	<ul style="list-style-type: none"> reacts neutrally physiologically safe not subject to hazard identification requirements
Measurements (l × w × h)	R 312: 120 × 25 × 4 – 6 R 380: 800 × 25 × 4 – 6
Description	retaining modules made of natural materials
Form	solid material
Colour	light yellow
Appearance	form stripes
Storage	Store in a dry place.
Safety instructions	Consult the safety data sheet for additional instructions.

E 824	
Application instructions	
<ul style="list-style-type: none"> The installed retaining modules must be impregnated with GEAQUELLO® E 824 according to the application ratio. Use gloves and eye protection while working. Cover the work place with paper or foil. 	
Product properties	<ul style="list-style-type: none"> reacts neutrally physiologically safe not subject to hazard identification requirements
Colour	blue
Viscosity	< 10 mPa·s
Density	approx. 1.1 g/cm³
pH value (10 % solution)	7.0–8.0
Conductivity (10 % solution)	450–600
Boiling point	approx. 100 °C
Melting point	approx. 0 °C
Storage	Protect from frost. Store in a cool and dry place. Storage life of at least 24 months in sealed original container.
Safety instructions	Consult the safety data sheet for additional instructions.