ROLF*KUHN*GMBH

member of svt group

Material of building material category B2 (normal flammability) according to DIN 4102-1

Product Description

KERAFIX® Flexting 100 is a flexible, intumescent material on the basis of expandable graphite, which expands with high pressure when heat is applied.



Application Areas

- Fire protection doors of steel or aluminium
- Safety storage cabinets, control cabinets
- In drywall construction: floor constructions

Technical Data

Composition: expanding construction material on the basis of expandable graphite

Material structure: firm, flexible roll material

Bulk density [kg/m³]: 1300 (±10 %) Start of reaction [°C]: from approx. 190

Expansion rate [x times]: 8 to 15 (450 °C; 30 min.; without load)

Direction of action: three-dimensional Expansion pressure [N/mm²]: at least 0.6

Design Variants

KERAFIX® Flexting 100 without additional lamination

Variant SK: single-sided adhesive

Further variants on request.

Supply Formats

Standard lengths: 25 000 mm and 50 000 mm

Widths: up to 320 mm

Thicknesses: 1.5 mm and 2.0 mm (special thicknesses available on request)

Special formats are available on request. The cut formats (lengths x widths) are manufactured on the basis of the general tolerance DIN ISO 2768-1-c. The formed parts and stamped parts are manufactured on the basis of the general tolerance DIN 7715-5-p2. Please observe the safety data sheet.

Note

The information in this brochure is based on our knowledge and experience to date. This information does not release the user from carrying out independent tests and trials due to the various influences when processing and applying our product. It is not possible to derive a guarantee of certain properties or suitability of the product in a concrete application case based on our information. All the descriptions, drawings, photographs, data, conditions, weights etc. included may change without previous announcement; they do not constitute the contractually agreed property of the product. The recipient of our product is responsible to observe any trademark rights and existing laws and regulations.

Page 1 of 1 Version 12/2021